

What is claimed is:

1. A safety winged set comprising:
 - a winged needle, provided with one lateral piece extending from two lateral sides of the winged needle body, respectively,
 - 5 wherein said winged needle body is fitted with an injection needle at the front end thereof, and a flexible tube is connected with the rear end of said winged needle ;
 - a winged needle cover, provided with several gliding slots on one or both sides thereof corresponding to the positions of said
 - 10 lateral pieces of said syringe, wherein on the upper end of one side gliding slot and the lower end of the other side gliding slot, an accommodating slot is provided, respectively, and said winged needle cover is provided with a holding portion on one side thereof.
2. The safety winged set according to claim 1, wherein said
- 15 lateral piece is provided on one lateral side of said winged needle body.
3. The safety winged set according to claim 1, wherein each lateral piece is provided with a bent portion adjacent to said winged needle body.
- 20 4. The safety winged set according to claim 1, wherein a protruding part is provided on the connecting portion of said accommodating slot and said gliding slot.
5. The safety winged set according to claim 1, wherein no accommodating slot is provided on the upper end of said winged
- 25 needle cover, said holding portion is provided with a protruding

fastener, and said lateral piece of said winged needle is provided with a fastening hole at a position corresponding to said protruding fastener.

6. The safety winged set according to claim 5, wherein said
5 fastening holes on said holding portion can be replaced by said protruding fastener, whereas said protruding fastener on said lateral piece can be replaced by said fastening hole.

7. The safety winged set according to claim 1, wherein a spring
is sleeved on the rear portion of said syringe, a ring portion is fixed
10 against the rear end of said spring, a hook extending from the rear end of said winged needle cover is engaged with the rear wall surface of said ring portion, and said winged needle cover is provided with a protruding block at the interior edge of the rear end thereof.

15 8. The safety winged set according to claim 1, wherein said winged needle cover is provided with a protruding block at the interior edge of the rear end thereof.

9. The safety winged set according to claim 1, wherein a spring
is sleeved on the rear portion of said syringe, a ring portion is fixed
20 against the rear end of said spring, several fastening holes are provided on said ring portion, said lateral piece of said winged needle is provided on said lateral side of said winged needle cover, several resilience pieces extending from the rear end of said winged needle cover have protruding fasteners on the interior edges at the
25 front and the rear ends thereof, respectively.

10. The safety winged set according to claim 9, wherein several protruding fastener are provided on said ring portion, and each resilience piece is provided with a fastening hole on the rear end thereof.

5 11. The safety winged set according to claim 9, wherein no fastening hole is provided on said ring portion, and said protruding fastener on the front and rear ends of said resilience piece is replaced by a hook.

12. The safety winged set according to claim 1, wherein said
10 holding portion of said winged needle cover is provided on the outer periphery of said syringe1, said lateral piece of said winged needle is provided on the lateral side of said winged needle cover, said winged needle cover is provided thereon with said gliding slot for said holding portion of said winged needle to penetrate
15 therethrough, at the front and the rear ends of said gliding slot, an accommodating slot is provided, respectively, and a protruding part is provided on the connecting portion of said accommodating slot and said gliding slot.

13. The safety winged set according to claim 12, wherein no
20 accommodating slot is provided on the front and the rear ends of said gliding slot of said winged needle cover, said lateral piece of said winged needle cover is provided with said fastening hole, said holding portion of said winged needle at its side edge is provided with said protruding fastener to be engaged with said fastening hole,
25 one or more fastening pieces are provided on the rear end of said gliding slot, and said fastening piece is provided with said fastening

hole to be engaged with the protruding fastener of said holding portion.

14. The safety winged set according to claim 13, wherein no accommodating slot is provided on said lateral piece of said winged
5 needle cover, at the rear end of said lateral piece on one side of said winged needle cover, a stopping piece extends upwardly therefrom, and only one side of said holding portion is provided with a protruding fastener at the position corresponding to said fastening hole of said fastening piece.

10 15. The safety winged set according to claim 14, wherein said lateral piece of said winged needle cover without said stopping piece is provided with a fastening aperture.

16. The safety winged set according to claim 13, wherein an aperture is provided on the lateral edge of said gliding slot and
15 extends to the lateral edge of said winged needle cover, a fastening piece is extended from said aperture, a stopping fastener is provided on said fastening piece, and said protruding fastener on said holding portion of the winged needle is replaced by said fastening hole.

17. The safety winged set according to claim 16, wherein no
20 fastening hole is provided on said holding portion of said syringe, no fastening piece and no aperture is provided on said winged needle cover, on the upper or lower end of said gliding slot adjacent to the rear end thereof, an accommodating slot is provided, and a protruding part is provided on the connecting portion of said
25 accommodating slot and said guiding slot.

18. The safety winged set according to claim 1, wherein said
gliding slot of said winged needle cover penetrates through the rear
end of said winged needle cover, said gliding slot is provided with a
stopping block at a position adjacent to the rear end thereof, the
5 front wall surface of said stopping block is perpendicular to said
gliding slot, and the rear wall surface of said stopping block is an
incline.

19. The safety winged set according to claim 1, wherein on the
upper end of said gliding slot of said winged needle cover, there is
10 a guiding track connected to a guiding slot, a protruding part is
provided on the connecting portion of said guiding track and said
gliding slot, and on the rear end of the gliding slot, a stopping
block is provided to partition an accommodating portion at the rear
end of said gliding slot.

15 20. The safety winged set according to claim 1, wherein the rear
end of said winged needle is connected to an inserting tube to be
inserted into said test tube via said flexible tube, and a clamp
portion is provided on the rear end of said inserting tube.

21. The safety winged set according to claim 20, wherein a test
20 tube cap is sleeved on the opening end of said test tube, several
claw-shaped clamping heads are provided on the rear end of said
test tube cap, said claw-shaped clamping heads compress with each
other to form seal, a guiding slot is provided on the front end of
said test tube cap and connected with the rear ends of said claw-
25 shaped clamping heads, and the wall surface of said guiding slot is
an incline tapered inwardly.

22. The safety winged set according to claim 21, wherein the outer periphery of said guiding slot is provided with a membrane.
23. The safety winged set according to claim 22, wherein said membrane at the outer periphery of said guiding slot is replaced by
5 a cap.
24. The safety winged set according to claim 1, wherein said lateral piece of said winged needle is provided with one or more suckers at the lower portion thereof, and said sucker is replaced by viscose or other adhesive materials having viscous properties.
- 10 25. The safety winged set according to claim 1, wherein said holding portion of said winged needle or said fastening piece of said winged needle cover is provided a sucker, and said sucker is provided on the rear and lower portion of said syringe.
26. The safety winged set according to claim 20, wherein no
15 clamp portion is provided at the rear end of said inserting tube, an interposing element is provided within said inserting tube, a holding element is provided around the periphery of said interposing element, said interposing element is provided with a flow-directing hole penetrating therethrough, a ring protruding
20 stopper is provided on the interior wall surface of said inserting tube at the front and rear ends of said holding element, and a non-return structure constructed of several blades is provided behind said ring protruding stopper at the rear end of said inserting tube.
27. The safety winged set according to claim 20, wherein no non-
25 return structure is provided within said inserting tube, a spring is

sleeved around the outer periphery of said inserting tube at the rear end thereof, the front end of said spring is connected to the rear end of said holding element of said interposing element, the rear end of said spring is fixed against the front end of said ring protruding stopper at the rear end of said inserting tube, and no flow-directing hole is provided on said interposing element.

28. The safety winged set according to claim 27, wherein no interposing element is provided within said inserting tube, no ring protruding stopper is provided on the interior wall of said inserting tube, and said non-return structure is directly provided on the interior wall of said inserting tube at the front end.

29. The safety winged set according to claim 28, wherein no interposing element is provided within said inserting tube, no ring protruding stopper is provided on the interior wall of said inserting tube, and said non-return structure is directly provided on the interior wall of said inserting tube at the front end.

30. The safety winged set according to claim 27, wherein said holding element is provided on the rear end or the middle outer periphery of said interposing element, and said ring protruding stopper at the front end of said holding element of said inserting tube extends to the front end of said inserting tube.

31. The safety winged set according to claim 1, wherein the outer periphery at the front end of said winged needle cover is attached thereto a bent piece, and a hemostatic cotton is connected to the upper end of said bent piece.

32. The safety winged set according to claim 31, wherein an inserting bar extends from the lower portion of said bent piece 211, and an inserting hole to be inserted by said inserting bar is provided on said winged needle cover.

5 33. The safety winged set according to claim 32, wherein said inserting bar at the lower portion of said bent piece is replaced by a hook, and a shaft bar to be engaged with said hook is provided on said winged needle cover 2.

34. The safety winged set according to claim 33, wherein a shaft
10 hole is provided at the lower portion of said bent piece to be sleeved on said shaft bar.